



ELMO

TD 22-52-62TS 60Hz/1709-26

U

V.le Certosa 8/B - 27100 Pavia Italy
Tel. + 39 382 529564 - 422372
Fax. + 39 382 527041
E-Mail: info@elmoitaly.com

SUBMERSIBLE MOTORS FOR HYDRAULIC LIFTS
UNTEROELMOTOREN FÜR HYDRAULISCHE AUFZÜGE
MOTORI IMMERSI PER ASCENSORI IDRAULICI



PERFORMANCE DATA SHEET


2 POLES 3 PHASE 60 Hz 460 V

Table with columns for Basic Part Number, Nominal Output, Nominal Torque, Nominal Current, Locked Rotor, kVA Code, Nominal Speed, Efficiency, BTU/HR, Power Factor, Rotor Inertia Moment, Output, Current, Speed, and Weight. Includes multiple rows of motor specifications.

THESE MOTORS ARE MADE ONLY ON SPECIFIC REQUEST

- FOR MOTORS WORKING INTO HYDRAULIC OIL AT 45°C (WITHOUT FLYWHEEL)
INCLUSIVE OF THE HYDRAULIC LOSSES DUE TO THE ROTATION INTO OIL AT 45°C (WITHOUT FLYWHEEL)
THE SELECTING OUTPUT CORRESPONDS TO A 30 PCT TORQUE OVERLOAD AND TO 3300 AT 60 Hz FICTITIOUS RPM.

Duty types at full-load: S2 30 min. For different operating conditions please contact us.
Betriebsarten bei Vollast: S2 30 min. Für unterschiedlichen Betriebsbedingungen wenden Sie sich bitte an uns.
Tipi di servizio a pieno carico: S2 30 min. Per condizioni operative differenti contattateci.



IN ANY MOMENT AND WITHOUT NOTICE ELMO CAN CHANGE MANUFACTURING PROCESS, PERFORMANCE FEATURES.
LA ELMO S.r.l. SI RISERVA IL DIRITTO DI APPORTARE QUALSIASI VARIAZIONE SENZA ALCUN PREAVVISO.