

**ELMO**

Tel. ++39 382 529564 - 422372

Fax. ++39 382 527041

V.le Certosa 8/B - 27100 Pavia Italy

E-Mail: info@elmoitaly.com

SUBMERSIBLE MOTORS FOR HYDRAULIC LIFTS

UNTEROELMOTOREN FUER HYDRAULISCHE AUFZUEGE

MOTORI IMMERSI PER ASCENSORI IDRAULICI

Tab.
S-Cap. 1604-04
3
CSA



IN ANY MOMENT AND WITHOUT NOTICE ELMO CAN CHANGE MANUFACTURING PROCESS, PERFORMANCE FEATURES.

TABLE CAPACITOR for: 2 Poles - Single Phase Motors - Size 3 - Without Flywheel

VOLTAGES	NOMINAL OUTPUT		Q.TY, COMBINATION AND CAPACITORS' TYPE	TOTAL CAP. VALUE		CAPACITORS' DIMENSIONS (mm)	
				μF 450V ₀	A	B	
	HP	KW					
200 - 208 V 60 Hz	2	1,5	N°1 80 μF	80	55	155	
	2,4	1,8	N°1 80 μF	80	55	155	
	3,6	2,6	N°2 60 μF	120	55	120	
	5	3,7	N°2 70 μF	140	55	155	
	6	4,4	N°2 80 μF	160	55	155	
	8	6	N°2 70 μF	220	55	155	
			N°1 80 μF				
	10	7,4	N°1 100 μF	250	55	155	
N°1 80 μF							
N°1 70 μF							

VOLTAGES	NOMINAL OUTPUT		Q.TY, COMBINATION AND CAPACITORS' TYPE	TOTAL CAP. VALUE		CAPACITORS' DIMENSIONS (mm)	
				μF 450V ₀	A	B	
	HP	KW					
220 - 230 V 60 Hz	2	1,5	N°1 80 μF	80	55	155	
	2,4	1,8	N°1 80 μF	80	55	155	
	3,6	2,6	N°1 100 μF	100	60	120	
	5	3,7	N°2 70 μF	140	55	155	
	6	4,4	N°2 80 μF	160	55	155	
	8	6	N°2 70 μF	220	55	155	
			N°1 80 μF				
	10	7,4	N°1 100 μF	250	55	155	
N°1 80 μF							
N°1 70 μF							

LA ELMO S.r.l. SI RISERVA IL DIRITTO DI APPORTARE QUALSIASI VARIAZIONE SENZA ALCUN PREAVVISO.

